

# LEBRAVO®

<b>Name of article:</b>	<b>Charm</b>
<b>Leather type:</b>	Performance Nubuck bovine leather with natural grain
<b>Average hide size:</b>	22-25 / 50-55 SqFt Half hides/ Full hides
<b>Thickness:</b>	1,3/1,4mm
<b>Tan Type:</b>	Chrome Tanning
<b>Characteristics:</b>	Wipeable, washable, stain resistant
<b>Origin:</b>	Europe, Tanned in Italy
<b>Embossing:</b>	No Embossing

Ideal for contract and hospitality project as well as residential

<b>Parameter Description</b>	<b>Unit of measure</b>	<b>Value</b>	<b>Method</b>
<i>Tear strenght</i>	<i>N</i>	<i>20</i>	UNI EN ISO 3377-1
<i>Dry rub fastness</i>	<i>Cycles</i> <i>Gray scale</i>	<i>500</i> <i>4/5</i>	UNI EN ISO 11640
<i>Wet rub fastness</i>	<i>Cycles</i> <i>Gray scale</i>	<i>100</i> <i>4/5</i>	UNI EN ISO 11640
<i>Artificial perspiration rubbing fastness</i>	<i>Cycles</i> <i>Gray scale</i>	<i>50</i> <i>5</i>	UNI EN ISO 11640
<i>Flexing endurance</i>	<i>Cycles</i>	<i>40000</i> <i>no break</i>	UNI EN ISO 5402-1
<i>Color fastness to light</i>	<i>Blue scale</i>	<i>5</i>	UNI EN ISO 105-B02
<i>Adhesion of finish</i>	<i>N</i>	<i>2</i>	UNI EN ISO 11644
<i>Color fastness to water spotting</i>	<i>Gray scale</i> <i>Min</i>	<i>5</i> <i>30</i>	UNI EN ISO 15700
<i>Fire behaviour</i>			BS5852 Pass CA TB 117

## **Cleaning and maintanance :**

1. In the event of a stain, quickly remove dirt with a cloth, taking care not to press to prevent it from penetrating inside the leather
2. For more intense stains, pour a little water with neutral soap (do not use invasive products: use specific products for leather care) or ethyl alcohol for stained marks
3. Dry with cloth, dabbing with delicate circular movements
4. Once dry, your leather will be as good as new!