

# LEBRAVO®

<b>Name of article:</b>	<b>Comfort</b>
<b>Leather type:</b>	Aniline bovine leather, soft suede with a velvety feel
<b>Average hide size:</b>	16 SqFt
<b>Thickness:</b>	1,2/1,4mm
<b>Tan Type:</b>	Chrome Tanning
<b>Characteristics:</b>	Not water resistant on standard article (Scotch guard protection available on request )
<b>Origin:</b>	Europe, Tanned in Italy
<b>Embossing:</b>	No Embossing

Ideal for residential project.

Parameter Description	Unit of measure	Value	Method
<i>Tear strenght</i>	<i>N</i>	<i>80</i>	UNI EN ISO 3377-2
<i>Dry rub fastness</i>	<i>Cycles</i> <i>Gray scale</i>	<i>50</i> <i>3</i>	UNI EN ISO 11640
<i>Wet rub fastness</i>	<i>Cycles</i> <i>Gray scale</i>	<i>20</i> <i>3</i>	UNI EN ISO 11640
<i>Tensile strenght</i>	<i>N/mm<sup>2</sup></i>	<i>10</i>	UNI EN ISO 3376
<i>Abrasion resistance (dry)</i> <i>Abrasion resistance (wet)</i>	<i>Cycles</i> <i>Cycles</i>	<i>25000 no break</i> <i>5000 no break</i>	UNI EN ISO 5402-1
<i>Adhesion of finish</i>	<i>N</i> <i>mm</i>	<i>4</i> <i>10mm</i>	UNI EN ISO 11644
<i>Water vapour permeability</i>	<i>mg/cm<sup>2</sup>h</i>	<i>5</i>	DIN 53333
<i>Fire behaviour</i>			BS5852 Pass

## Cleaning and Maintanance:

Dust with a soft dry cloth, do not use chemical products.