

# LEBRAVO®

<b>Name of article:</b>	<b>Dali</b>
<b>Leather type:</b>	Semi aniline bovine leather
<b>Average hide size:</b>	22 SqFt Half hides
<b>Thickness:</b>	1,3/1,5mm
<b>Tan Type:</b>	Chrome Tanning
<b>Characteristics:</b>	Wipeable
<b>Origin:</b>	Europe, Tanned in Italy
<b>Embossing:</b>	With embossing

Ideal for contract and hospitality project as well as residential

<b>Parameter Description</b>	<b>Unit of measure</b>	<b>Value</b>	<b>Method</b>
<i>Tear strenght</i>	<i>N</i>	45	UNI EN ISO 3377-2
<i>Dry rub fastness</i>	<i>Cycles</i> <i>Gray scale</i>	150 3	UNI EN ISO 11640
<i>Wet rub fastness</i>	<i>Cycles</i> <i>Gray scale</i>	50 3	UNI EN ISO 11640
<i>Abrasion resistance</i>	<i>Gray scale</i>	6400 <i>Cycles</i> <i>no abrasion</i>	UNI EN ISO 13520
<i>Dry flexing endurance</i> <i>Wet flexing endurance</i>	<i>Cycles</i> <i>Cycles</i>	50000 <i>no break</i> 20000 <i>no break</i>	UNI EN ISO 5402-1
<i>Color fastness to light</i>	<i>Blue scale</i>	4	UNI EN ISO 105-B02
<i>Adhesion of finish</i>	<i>N/10mm</i>	2	UNI EN ISO 11644
<i>Color fastness to water spotting</i>	<i>Gray scale</i> <i>Min</i>	4 30	UNI EN ISO 15700
<i>Fire behaviour</i>			BS5852 Pass

## **Cleaning and Maintanance:**

Dust with a soft damp cloth, do not use chemical products.