

LEBRAVO®

Name of article:	Touch
Leather type:	Goat suede leather
Average hide size:	4 SqFt Full hides
Thickness:	0,7-1,0mm
Tan Type:	Chrome Tanning
Characteristics:	Suede. Not water resistant on standard article (Scotch guard protection available on request)
Origin:	Europe, Tanned in Italy
Embossing:	No Embossing

Ideal for small items and panelling

Parameter Description	Unit of measure	Value	Method
<i>Tear strenght</i>	<i>N</i>	<i>1200</i>	UNI EN ISO 3377-2
<i>Dry rub fastness</i>	<i>Cycles</i> <i>Gray scale</i>	<i>50</i> <i>3</i>	UNI EN ISO 11640
<i>Wet rub fastness</i>	<i>Cycles</i> <i>Gray scale</i>	<i>20</i> <i>3</i>	UNI EN ISO 11640
<i>Dry flexing endurance</i> <i>Wet flexing endurance</i>	<i>Cycles</i> <i>Cycles</i>	<i>20000 no break</i> <i>5000 no break</i>	UNI EN ISO 5402-1
<i>Color fastness to light</i>	<i>Blue scale</i>	<i>3/4</i>	UNI EN ISO 105-B02
<i>Fire behaviour</i>			BS5852 Pass

Cleaning and Maintanance:

Dust with a soft dry cloth, do not use chemical products.